



Upon activation EXTINGO quickly transforms an inert, solid compound into a rapidly expanding cloud of harmless, micro-solid particles of potassium salts. These particles react instantly with the free radicals in the air that cause combustion, when breaking the combustion chain, the fire is extinguished swiftly!

An additional benefit is that the micro-particles also absorb the fire's heat when the fire is out, they remain as a fine dust, protecting against re-ignition until easily brushed away. They do not harm people or the environment, and do not damage equipment which can continue to work even when the fire is out.

This EXTINGO Aerosol Fire Extinguisher is an effective replacement to the Halon, Carbon Dioxide (CO2), dry powder and other dangerous and harmful extinguishing agents, offering significant advantages in performance, size, weight, high warranty periods with low maintenance costs. They have **zero** effects on the **environment** and do not contribute to the destruction of the ozone.

PORTABLEFIRE PROTECTION UNITS



Applications: Engines, electrical and electronic appliances, plastics, furniture, cooker, firewood, etc.





















EXIMED

PORTABLEFIRE PROTECTION UNITS











- 1. Hold the EXTINGO from the plastic handle and take out the upper tube.
- 2. Introduce the upper tube in the lower part of the handle using it like an extension.
- 3. Hold the EXTINGO by the plastic handle and tear off the protective ring.
- 4. Direct the jet toward the base of the flames (minimum distance 60cm).

HAND-HELD FIRE EXTINGUISHER EXTINGO 50 & 100 MODEL'S

USE:

- It is a manual and portable fire extinguishing device with a large capacity and a wide flexibility of use.
- It has the characteristics of being eco-friendly and non-toxic.
- It is used to extinguish fires of flammable solids, flammable liquids, electrical and electronic equipment.
- It features an extension handle, to increase the length as a safety feature.
- EXTINGO is practical with a fast activation system
- 5 years warranty
- Do not use after expiry date. Use under 18 years.

TECHNICAL DATA:

- Version 50 and 100 seconds
- Dimension: 42 x 263mm
- **Dimension:** in use 42 x 358mm
- To release, tear off the protective ring
- Weight: 415gr and 490gr
- Duration time 50 and 100 seconds
- Extinguishing charge 110 and 190gr
- Aerosol temperature >90*C

WARNING:

- The working device produces high temperature of aerosol
- Do not touch the metal tube during and after use
- Do not point the jet of aerosol towards people
- In case of accidental activation wait for the complete jet release of aerosol into the environment
- Do not use the device if it is damaged
- Do not disassemble the device
- Keep this device out of the reach of children

DISPOSAL:

- Disposal of the product and packaging must be carried out in accordance with national regulations.
- Kindly contact your local supplier / agent

CLASSIFICATION AND CERTIFICATION CE:

CE Module B: LOM 13PIRO1254 CE Certification nr: 0163-1545



Imported By



Alltec Fire Protection Products & Services Ltd

Authorised Distributor:



Lysismart Solutions Ltd info@lysimart.com Tel. 25877545 / 99442353



